

THE HOTSY TOP-LOADING AUTOMATIC PARTS WASHERS



A better way to clean parts.

Welcome to the future of parts cleaning

Faster, easier, safer than solvents

Manual scrubbing with solvents and brushes just can't compare to the speed and ease of cleaning with a Hotsy automatic parts washer. With Hotsy, you can say goodbye to dirty, time-consuming manual parts cleaning. Now, trained technicians can concentrate on more productive work.

Environmentally friendly

Hotsy automatic parts washers are based on safe aqueous cleaning, so you eliminate the potential health hazards and disposal problems related to solvent use...something more and more states are outlawing altogether.

Effective

A Hotsy automatic parts washer is like a super-industrial-strength dishwasher. It combines hot water and modern detergents to give you cleaning action that's far more powerful than any solvent.



Model 7320
(Shown with optional Power Brush & Timer)

Powerful jets of detergent and water remove grease, oil and dirt quickly and efficiently. The bottom line is a far more cost-effective parts-washing solution.

Superior to other aqueous cleaning systems

Compare Hotsy features with other automatic parts washers and you'll see why Hotsy parts washers are the preferred solution. Their rugged design delivers outstanding reliability in industrial environments. Small footprints save valuable floor space. And automatic controls make them easy to operate.

Exceptional value

With Hotsy, you get more than your money's worth. That's because the Hotsy parts washers give you extra cleaning features at no extra cost. These include an integrated oil-removal system, easy access debris screen and durable wheels for greater mobility.

Detergents designed specifically for parts cleaning in Hotsy machines

In addition to our large family of automatic parts washers, Hotsy offers a complete line of biodegradable TubMate detergents to give you a complete parts-washing solution. TubMate detergents are specially formulated to give you the best cleaning action at temperatures as low as 110° F, which means significant savings in energy costs. And they include a superb blend of corrosion inhibitors to protect your clean parts and your automatic parts washer's metal surfaces from rust and corrosion.

Hotsy TubMate detergents are also safe to use because they contain no caustic soda, caustic potash, phenolics, chlorinated solvents or heavy metals. And they're highly concentrated, which means a little goes a long way.

Choose from one of these highly effective formulations:



All-Purpose Detergent*

Appropriate for virtually any type of part, including iron, steel, soft metals and plastics. Also available in liquid form.

*USDA Approved.



Steel & Iron Cleaner

A heavy-duty liquid cleaner that's perfect for trucking, manufacturing, railroads, food processing, bakery and other industries that require the removal of heavy grease, baked-on carbon, loose paint and coatings.



Aluminum & Alloy Cleaner

A specially formulated cleaner for soft metals and alloys such as aluminum, magnesium, brass, nickel, zinc, etc.




Phosphatizer/Cleaner

A complete detergent and phosphatizing system for cleaning metal parts and preparing them for painting.

Features for the Models 7230 and 7320 Parts Washers include:



Durable machined-sheave chain drive for turntable is designed for increased safety and longevity, plus it prevents the risk of binding or breaking.



Hand detail brush (optional) speeds cleaning of blind holes and recesses. Shown with small parts basket (standard).



Control panel includes 60-minute washer timer, 12-hour heater timer, 30-minute oil skimmer timer, turntable off/on switch and low-water alert light.

Thermostatically controlled heater maintains optimum cleaning temperature.



Low-water shutoff protects heating elements in case water level drops.

Rugged construction and durable finish stands up to heavy industrial use.



Sump access panels make for easier sump clean-out.

Heavy-duty wheels allow machine to be easily moved.



Control panel includes 60-minute wash timer, 12-hour heater timer, turntable off/on switch and low-water alert light.



Model 7320
Load Capacity: 750 lbs.
(Shown with optional power brush and 2-channel timer)



Model 7230
Load Capacity: 500 lbs.



Easy access debris screen prevents foreign objects and small parts from falling into sump.




Built-in oil skimmer with oil-drain container removes oil from cleaning solution in sump (Model 7320 only).

4" Containment ring secures parts on turntable.



Power scrub brush (optional) makes short work of stubborn gasket material and baked-on carbon (shop air required).



Oil decant system with oil-drain container allows removal of oil from sump (Model 7230 only).



All Hotsy Top-Loading Parts Washers are ETL-Certified to UL-73 Standards and to CSA-22.2 #68

Backed by Hotsy... America's #1 manufacturer of cleaning systems

Hotsy has built its excellent reputation on quality products, plus outstanding local service and support. Our success depends on customer satisfaction. And with our nationwide network of authorized Hotsy Dealers, we've been satisfying customers with reliable, effective cleaning solutions for more than 30 years.



Have other parts-washing requirements?

Ask your Hotsy representative about our family of front-loading (large capacity) models.

Call for a demo

Watching a Hotsy automatic parts washer in action is a sure way to see for yourself that Hotsy offers a better solution than solvent-based cleaning methods or other aqueous systems. We'll be happy to come to your facility and show how a Hotsy machine performs in your environment, cleaning your actual parts.

Call 1-800-525-1976 today for the location of your nearest Hotsy Dealer or visit our website at: www.hotsy.com



Model 7230 / S7230-1



Model 7320

(Shown with optional power brush & timer)

SPECIFICATIONS	Top-Loading Automatic Parts Washers
Load Height:	Model 7230 / S7230-1: 16" Model 7320: 18"
Turntable Diameter:	Model 7230 / S7230-1: 22" Model 7320: 25"
Turntable Load Capacity:	Model 7230 / S7230-1: 500 lbs. Model 7320: 750 lbs.
Water Pump Volume:	Model 7230 / S7230-1: 28 GPM; 1680 GPH Model 7320: 50 GPM; 3000 GPH
Water Pump Pressure:	Model 7230 / S7230-1: 30 PSI Model 7320: 45 PSI
Water Pump:	Model 7230 / S7230-1: Close-Coupled, Sealed. Model 7320: Centrifugal, Vertical, Sealless.
Power/Pump Motor:	Model 7230: 1 HP, 230V, 1PH, 60-cycle, 7.2 Amp. (24 total Amps.); open, drip proof. Model S7230-1: 1 HP, 115V, 1PH, 60-cycle, 14.2 Amp. (15 total Amps.); open, drip proof. Model 7320: 3 HP, 230V, 1PH, 60-cycle, 13 Amp. (40 total Amps.); totally enclosed, fan cooled (TEFC). <i>Other voltages available for both models upon request.</i>
Water Heater:	Submerged Calrod-type; electric; fused; equipped with adjustable thermostat; automatic low-water shutdown (both models). Model 7230: 4.5 kW, up to 194°F Model S7230-1: 2 kW, up to 150°F Model 7320: 6 kW, up to 194°F
Sump Capacity:	Model 7230 / S7230-1: 25 gallons Model 7320: 50 gallons
Spray Bars:	Model 7230 / S7230-1: Top, side and bottom with seven nozzles. Model 7320: Top, side and bottom with nine nozzles.
Oil Removal:	Model 7230 / S7230-1: Built-in oil decant system. Model 7320: Built-in oil skimmer.
Turntable Drive:	AC gear motor with chain and torque limiter; thermally protected.
Controls:	Models 7230/7320: 60-minute wash timer; 12-hour heater timer; turntable on/off switch; low-water light; 30-minute oil skimmer timer (Model 7320 only). Model S7230-1: 15-minute wash time; lighted on/off heater switch; turntable on/off switch and low-water light.
Construction:	12-gauge steel sump, 14-gauge steel cabinet and lid with baked-on, automotive-style finish.
Standard Features:	4" containment ring; oil container and small parts basket.
Optional Accessories:	Power scrub brush kit; hand detail brush kit; 7-day timer; filtration; stainless steel construction & automatic water fill.
Dimensions:	Model 7230 / S7230-1: L-44" (111.76 cm), W-34" (86.36 cm), H-50" (127 cm). Model 7320: L-51" (129.54 cm), W-36" (91.44 cm), H-50.5" (128.27 cm).
Shipping Weight:	Model 7230 / S7230-1: 400 lbs. Model 7320: 620 lbs.



(800) 525-1976 Fax: (888) 880-9631 Built with PRIDE in the USA 
www.hotsy.com e-mail: info@hotsy.com
 P/N 97-0421E Effective 11/03 Supercedes 768686D (4/03)
 Specifications and product descriptions subject to change without notice. © 2003 Hotsy



All Hotsy Top-Loading Automatic Parts Washers are ETL-Certified to UL-73 Standards and to CSA-22.2 #68